

Push Trolley

ALMET

Main features

- Robust design for a trully long lasting operation.
- Wheels are equipped with two sealed , lubricated, precision ball bearings that require no relubrication.
- Frames connected by hardened axle, secured by two nuts on each side. Side plates formed to protect the trolley.
- Trolley is able to roll on IPS or IPR beam type.
- Spacer whasers included to shift inside and outside for adjustment to wide range of beams.
- To be used with hook suspended hoist.
- Made in Mexico.



Specifications and weights

Capacities: 1/2 - 20 (tons)

(tons.)	(lbs.)	(in.)	(in.)	(in.)
Capacity	Weight	Depth of beam	Flange width	Min. Radius Curve
1/2	26.46	3"-12"	2.3"-4.5"	45"
1	55.11	5" - 18"	3"-7"	53"
2	81.57	6"-24"	4"-8.5"	64"
3	125.66	6"-24"	4"-8.5"	73"
5	154.32	6"-24"	4.25" - 8.5"	88"
10	330.69	12"-24"	4.7" - 11"	127"
15	518.09	12"-24"	5.5" - 11"	136"
20	760.59	14"-24"	6.5" 11"	150"

Caution

- * Do not exceed the capacity of the trolley
- * Do not use to lift people or carry load above them.
- * To be used with proper material handling equipment and accessories.
- *The equipment illustrated and described is designed for manual operation only.

(tons.)	A	B	C	D	E	F	G	H
1/2	3"	3.5"	0.9"	.875"	10.1"	4.7"	10.4"	7"
1	4.1"	5"	1.2"	1"	12.8"	6"	12.6"	7.7"
2	5"	5.7"	1.2"	1.25"	15"	7.7"	15"	8.7"
3	5.4"	6.3"	1.5"	1.5"	17"	9.5"	16.7"	10.4"
5	5.8"	6.8"	1.5"	1.5"	20"	10.4"	19"	12.4"
10	6.5"	8.3"	2.1"	2"	24"	12"	25"	16"
15	7.9"	9.8"	2.5"	2.5"	26.5"	12.25"	27.25"	17.5"
20	9.4"	11.2"	3"	3"	29.5"	13.5"	30.2"	19"

