

Push Trolley ECOMET

Main features

- Designed with three axles for added strength and durability.
- Sealed and prepacked bearings with lifetime lubricant.
- Steel side plates formed to include trolley guards.
- Hardened wheels with shielded ball bearings that should not require further relubrication.
- Spacer washers can be shifted inside or outside for an easy adjustment to wide range of IPS and IPR beams.
- To be used with hook suspended hoist.
- Made in Mexico.



Capacities: 1/4 - 5 (tons)

Specifications and weights

(tons.)	(lbs.)	(in.)	(in.)	(in.)
Capacity	Weight	Depth of beam	Flange width	Min. Radius Curve
1/4	4.8	3" - 8"	2.500"-3"	36"
1/2	5	3" - 8"	2.500"-3"	36"
1	10.4	4" - 9"	2.875"-4"	46"
2	12.4	4" - 12"	3.500"-4.750"	46"
3	23.8	5" - 18"	3.750"-5.875"	53"
5	46	6" - 24"	4.750"-8.875"	88"

Caution

- * Do not exceed the capacity of the trolley
- * Do not use to lift people or carry load above them.
- * To be used with proper material handling equipment and accessories.
- * The equipment illustrated and described is designed for manual operation only.

Clearance dimensions (in.)

(tons.)	A	B	C	D	E	F	G	H
Capacity	A	B	C	D	E	F	G	H
1/4	2.175"	3"	0.825"	0.750"	8.125"	4.625"	7.875"	4.500"
1/2	2.175"	3"	0.825"	0.750"	8.125"	4.625"	7.875"	4.500"
1	3.175"	3.900"	1.250"	0.875"	10.500"	6.125"	10.125"	6.500"
2	3.175"	3.900"	1.250"	1"	10.625"	6.250"	13"	9"
3	4.450"	5.200"	1.250"	1.250"	12.625"	11.125"	14.500"	9.250"
5	4.800"	5.750"	1.600"	1.500"	17"	8.750"	21"	14"

